

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

FUGALITE BIO (A)

Date of first edition: 5/11/2022

Safety Data Sheet dated 11/28/2022

version 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: FUGALITE BIO (A)

Trade code: B0045 .053

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Epoxy coating

Uses advised against: Data not available.

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel. +39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Kerakoll Italy - +39-0536-816511

Ireland

Poison information centre: 01 809 2166 (Daily 8am-10pm)

In case of emergency call 999 or 112

Malta

In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Irrit. 2	Causes skin irritation.
Eye Irrit. 2	Causes serious eye irritation.
Skin Sens. 1B	May cause an allergic skin reaction.
Aquatic Chronic 3	Harmful to aquatic life with long lasting effects.

DECL10 This titanium dioxide-containing product is not classified as carcinogen by inhalation because it does not meet the criteria stated in Note 10, Annex VI of Regulation (EC) 1272/2008.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Pictograms and Signal Words



Warning

Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P280	Wear protective gloves and eye protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

EUH212	Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
--------	--

Contains

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
bis-[4-(2,3-epoxipropoxy)phenyl]propane
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$.

Other Hazards: Prolonged exposition and/or intensive inhalation of respirable free crystalline silica can cause pulmonary fibrosis commonly referred to as silicosis.

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: FUGALITE BIO (A)

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
10-19,9 %	bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS:1675-54-3 EC:216-823-5 Index:603-073-00-2	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411, M-Chronic:1 Specific Concentration Limits: C $\geq 5\%$: Eye Irrit. 2 H319 C $\geq 5\%$: Skin Irrit. 2 H315	01-2119456619-26
5-9,9 %	titanium dioxide	CAS:13463-67-7 EC:236-675-5 Index:022-006-00-2	EUH212	
2,5-4,9 %	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS:68609-97-2 EC:271-846-8 Index:603-103-00-4	Skin Irrit. 2, H315; Skin Sens. 1B, H317	01-2119485289-22
1-2,4 %	Alcohols, C12-15, branched and linear, ethoxylated	CAS:106232-83-1	Acute Tox. 4, H302; Eye Dam. 1, H318; Aquatic Chronic 3, H412	
< 1 %	Quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372	
< 0,5 %	1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	CAS:1065336-91-5 EC:915-687-0	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Repr. 2, H361; Skin Sens. 1A, H317, M-Chronic:1, M-Acute:1	01-2119491304-40-XXXX

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

- None in particular.

5.2. Special hazards arising from the substance or mixture

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.

5.3. Advice for firefighters

- Use suitable breathing apparatus .
 - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 - Move undamaged containers from immediate hazard area if it can be done safely.
-

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- Wear personal protection equipment.
- Remove persons to safety.
- See protective measures under point 7 and 8.

6.2. Environmental precautions

- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Retain contaminated washing water and dispose it.
- In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
- Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

- Suitable material for taking up: absorbing material, organic, sand
- Wash with plenty of water.

6.4. Reference to other sections

- See also section 8 and 13
-

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Avoid contact with skin and eyes, inhalation of vapours and mists.
- Do not eat or drink while working.
- See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

Component	OEL Type	Country	Ceiling	Long Term mg/m ³	Long Term ppm	Short Term mg/m ³	Short Term ppm	Notes
Quartz	NATIONAL	AUSTRALIA		0.100				Respirable fraction
	NATIONAL	AUSTRIA		0.150				Respirable aerosol
	NATIONAL	BELGIUM		0.100				
	NATIONAL	CANADA		0.100				Canada Ontario; Respirable aerosol
	NATIONAL	CANADA		0.100				Canada Quebec
	NATIONAL	DENMARK		0.300		0.600		Inhalable aerosol
	NATIONAL	DENMARK		0.100		0.200		Respirable aerosol
	NATIONAL	FINLAND		0.050				Respirable fraction
	NATIONAL	FRANCE		0.100				Respirable aerosol
	NATIONAL	HUNGARY		0.150				Respirable aerosol
	NATIONAL	IRELAND		0.100				Respirable fraction
	NATIONAL	NEW ZEALAND		0.200				Respirable aerosol
	NATIONAL	CHINA		1.000				Inhalable fraction. 10% <= free SiO2 <= 50%.
	NATIONAL	CHINA		0.700				Inhalable fraction. 50% < free SiO2 <= 80%.
	NATIONAL	CHINA		0.500				Inhalable fraction. Free SiO2 < 80%.
	NATIONAL	SINGAPORE		0.100				Respirable aerosol.
	NATIONAL	SPAIN		0.100				Respirable fraction
	NATIONAL	SWEDEN		0.100				Respirable aerosol
	NATIONAL	SWITZERLAND		0.150				Respirable aerosol
	NATIONAL	NETHERLANDS		0.075				Respirable dust
	NATIONAL	ITALY		0.050				Silice cristallina
	NATIONAL	ITALY		0.025				A2
	NATIONAL	ITALY		10.000				Come particelle non altrimenti specificate PNOC
	NATIONAL	KOREA, REPUBLIC OF		0.050				
	NATIONAL	UNITED STATES OF AMERICA		0.050				NIOSH
	NATIONAL	ARGENTINA		0.050				
	NATIONAL	CHILE		0.080				
NATIONAL	CROATIA		0.100					
NATIONAL	ESTONIA		0.100					

	NATIONAL	INDIA	10.000		
	NATIONAL	LITHUANIA	0.100		
	NATIONAL	MALAYSIA	0.100		
	NATIONAL	MEXICO	0.025		Respirable fraction
	NATIONAL	NORWAY	0.300		Total dust
	NATIONAL	NORWAY	0.100		Respirable dust
	NATIONAL	POLAND	0.100		Respirable fraction
	NATIONAL	PORTUGAL	0.025		Respirable fraction
	NATIONAL	SLOVENIA	0.050	0.400	
	NATIONAL	SOUTH AFRICA	0.100		
	ACGIH	NNN	0.025		(R), A2 - Pulm fibrosis, lung cancer
bis-[4-(2,3-epoxipropoxy)phenyl]propane	NATIONAL	NETHERLANDS	5.000		respirable fraction
	NATIONAL	NETHERLANDS	10.000		Inhalable fraction
titanium dioxide	NATIONAL	AUSTRALIA	10		
	NATIONAL	BELGIUM	10.000		
	NATIONAL	CANADA	10.000		Ontario
	NATIONAL	CANADA	10.000		Quebec
	NATIONAL	DENMARK	6.000	12.000	Long term and short term: total dust
	NATIONAL	FRANCE	11.000		Inhalable aerosol
	NATIONAL	GERMANY	0.300	2.400	DFG; Long term and short term: excluding ultrafine particles; respirable fraction; multiplied by the material density;
	NATIONAL	IRELAND	10.000		Inhalable fraction
	NATIONAL	IRELAND	8.000		Respirable fraction
	NATIONAL	JAPAN	0.300		JSOH; Nanoparticle, as Ti
	NATIONAL	LATVIA	10.000		
	NATIONAL	NEW ZEALAND	10000.000		The value for inhalable dust containing no asbestos and less than 1% free silica
	NATIONAL	CHINA	8.000		Inhalable fraction
	NATIONAL	POLAND	10.000	30.000	
	NATIONAL	ROMANIA	10.000	15.000	
	NATIONAL	SINGAPORE	10.000		
	NATIONAL	KOREA, REPUBLIC OF	10.000		
	NATIONAL	SPAIN	10.000		Inhalable aerosol
	NATIONAL	SWEDEN	5.000		Inhalable aerosol
	NATIONAL	SWITZERLAND	3.000		Respirable aerosol
	NATIONAL	UNITED STATES OF AMERICA	15.000		OSHA; total dust
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	10.000		Inhalable aerosol

	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	4.000		Respirable aerosol
	NATIONAL	ITALY	10.000		
	NATIONAL	ARGENTINA	10.000		
	NATIONAL	AUSTRIA	5.000	10.000	
	NATIONAL	BULGARIA	10.000		
	NATIONAL	CROATIA	10.000		total dust
	NATIONAL	CROATIA	4.000		respirable dust
	NATIONAL	GREECE	10.000		
	NATIONAL	GREECE	50.000		
	NATIONAL	GREECE	5.000		
	NATIONAL	INDONESIA	10.000		
	NATIONAL	LITHUANIA	5.000		
	NATIONAL	MALAYSIA	10.000		
	NATIONAL	MEXICO	10.000		
	NATIONAL	NORWAY	5.000		
	NATIONAL	PORTUGAL	10.000		
	NATIONAL	RUSSIAN FEDERATION	10.000		
	NATIONAL	SLOVAKIA	5.000		
	NATIONAL	SLOVENIA	6.000		
	NATIONAL	SOUTH SUDAN	10.000		Inhalable fraction
	NATIONAL	SOUTH SUDAN	5.000		Respirable fraction
	NATIONAL	TAIWAN, PROVINCE OF CHINA	10.000		
Quartz	ACGIH	NNN	10.000		A4 - LRT irr
	NATIONAL	AUSTRALIA	0.100		Respirable fraction
	NATIONAL	AUSTRIA	0.150		respirable aerosol
	NATIONAL	BELGIUM	0.100		
	NATIONAL	CANADA	0.100		Canada Ontario. Respirable aerosol
	NATIONAL	CANADA	0.100		Canada Quebec
	NATIONAL	DENMARK	0.300	0.600	Inhalable aerosol
	NATIONAL	DENMARK	0.100	0.200	Respirable aerosol
	NATIONAL	FINLAND	0.050		Respirable fraction
	NATIONAL	FRANCE	0.100		Respirable aerosol
	NATIONAL	HUNGARY	0.150		Respirable aerosol
	NATIONAL	IRELAND	0.100		Respirable fraction
	NATIONAL	NEW ZEALAND	0.200		Respirable aerosol
	NATIONAL	CHINA	1.000		Inhalable fraction. 10% <= free SiO2 <= 50%.
	NATIONAL	CHINA	0.700		Inhalable fraction. 50% < free SiO2 <= 80%.
	NATIONAL	CHINA	0.500		Inhalable fraction. Free SiO2 < 80%.
	NATIONAL	SINGAPORE	0.100		Respirable aerosol.

	NATIONAL	SPAIN	0.100		Respirable fraction
	NATIONAL	SWEDEN	0.100		Respirable aerosol
	NATIONAL	SWITZERLAND	0.150		Respirable aerosol
	NATIONAL	NETHERLANDS	0.075		Respirable dust
	NATIONAL	ITALY	0.050		Silice cristallina
	NATIONAL	ITALY	0.025		A2
	NATIONAL	UNITED STATES OF AMERICA	0.050		NIOSH
	NATIONAL	KOREA, REPUBLIC OF	0.050		
	NATIONAL	ARGENTINA	0.050		
	NATIONAL	CHILE	0.080		
	NATIONAL	CROATIA	0.100		
	NATIONAL	ESTONIA	0.100		
	NATIONAL	INDIA	10.000		
	NATIONAL	LITHUANIA	0.100		
	NATIONAL	MALAYSIA	0.100		
	NATIONAL	MEXICO	0.025		Respirable fraction
	NATIONAL	NORWAY	0.300		Total dust
	NATIONAL	NORWAY	0.100		Respirable dust
	NATIONAL	POLAND	0.100		Respirable fraction
	NATIONAL	PORTUGAL	0.025		
	NATIONAL	SLOVENIA	0.050	0.400	
	NATIONAL	SOUTH AFRICA	0.100		
	ACGIH	NNN	0.025		(R), A2 - Pulm fibrosis, lung cancer
	EU	NNN	0.100		(R), A2 - Pulm fibrosis, lung cancer
silicon dioxide, chemically prepared	NATIONAL	AUSTRALIA	2.000		This value is for inhalable dust containing no asbestos and < 1% crystalline silica
	NATIONAL	AUSTRIA	4.000		Inhalable aerosol
	NATIONAL	BELGIUM	10.000		
	NATIONAL	CANADA	10.000		Ontario
	NATIONAL	CANADA	6.000		Quebec
	NATIONAL	DENMARK	2.000	4.000	Inhalable aerosol
	NATIONAL	FINLAND	5.000		
	NATIONAL	GERMANY	4.000		AGS; Inhalable aerosol
	NATIONAL	GERMANY	4.000		DFG; Inhalable aerosol
	NATIONAL	IRELAND	6.000		Inhalable fraction
	NATIONAL	IRELAND	2.400		Respirable fraction
	NATIONAL	LATVIA	1.000		
	NATIONAL	NEW ZEALAND	1.000		
	NATIONAL	CHINA	2.000		Inhalable fraction
	NATIONAL	SINGAPORE	10.000		
	NATIONAL	KOREA, REPUBLIC OF	10.000		
	NATIONAL	SWITZERLAND	4.000		Inhalable aerosol

		ND			
	NATIONAL	UNITED STATES OF AMERICA	80.000		OSHA; 80/ % silica total dust (MG3)
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	6.000		Inhalable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	2.400		Respirable aerosol
	NATIONAL	ESTONIA	2.000		
	NATIONAL	SLOVENIA	4.000		Inhalable fraction
	NATIONAL	SOUTH AFRICA	6.000		Inhalable particulate
	NATIONAL	SOUTH AFRICA	3.000		Respirable particulate
Aluminium oxide	NATIONAL	FRANCE	10.000		Respirable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	10.000		Inhalable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	4.000		Respirable aerosol
	NATIONAL	AUSTRALIA	10.000		Inhalable dust containing no asbestos and < 1% crystalline silica
	NATIONAL	AUSTRIA	10.000	20.000	Long term: inhalable fraction; Short term: inhalable fraction, 60 minutes average value
	NATIONAL	AUSTRIA	5.000	10.000	Long term: respirable fraction; Short term: respirable fraction, 60 minutes average value
	NATIONAL	CANADA	10.000		
	NATIONAL	DENMARK	5.000	10.000	Calculated as Al; Long term and Short term: inhalable aerosol
	NATIONAL	DENMARK	2.000	4.000	Calculated as Al; Long term and Short term: respirable aerosol
	NATIONAL	GERMANY	4.000		Inhalable aerosol
	NATIONAL	GERMANY	1.500		Respirable aerosol
	NATIONAL	HUNGARY	6.000		Respirable aerosol
	NATIONAL	IRELAND	10.000		Inhalable fraction
	NATIONAL	IRELAND	4.000		Respirable fraction
	NATIONAL	LATVIA	6.000		

NATIONAL	NEW ZEALAND	10.000				The value for inhalable dust containing no asbestos and less than 1% free silica
NATIONAL	POLAND	2.500		16.000		Aluminium trioxide as Al fume; Long term: total dust fume
NATIONAL	POLAND	1.200				Aluminium trioxide as Al fume; Long term: respirable dust
NATIONAL	ROMANIA	2.000	0.500	5.000	1.200	Long term and short term: aerosol
NATIONAL	SINGAPORE	10.000				
NATIONAL	KOREA, REPUBLIC OF	10.000				
NATIONAL	SPAIN	10.000				Inhalable aerosol
NATIONAL	SPAIN	5.000				Respirable aerosol
NATIONAL	SWEDEN	5.000				Inhalable aerosol
NATIONAL	SWEDEN	2.000				Respirable aerosol
NATIONAL	SWITZERLAND	3.000				Respirable aerosol
NATIONAL	UNITED STATES OF AMERICA	15.000				OSHA; Total dust
NATIONAL	UNITED STATES OF AMERICA	5.000				OSHA; Inhalable dust

Predicted No Effect Concentration (PNEC) values

Component	CAS-No.	PNEC Limit	Exposure Route	Exposure Frequency
bis-[4-(2,3-epoxipropoxy)phenyl] propane	1675-54-3	0.006 mg/l	Freshwater	
		600.000 ng/L	Marine water	
		0.996 mg/kg	Freshwater sediments	
		0.099 mg/kg	Marine water sediments	
		0.196 mg/kg	Soil	
		10.000 mg/l	Microorganisms in sewage treatments	
		0.018 mg/l	Intermittent releases (freshwater)	
titanium dioxide	13463-67-7	0.184 mg/l	Freshwater	
		0.018 mg/l	Marine water	
		1.000 mg/kg	Intermittent releases (freshwater)	
		100.000 mg/kg	Intermittent releases (marine water)	
		100.000 mg/kg	Microorganisms in sewage treatments	
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	0.007 mg/l	Freshwater	
		0.072 µg/l	Marine water	
		10.000 mg/l	Microorganisms in sewage treatments	
		66.770 mg/kg	Freshwater sediments	
		6.677 mg/kg	Marine water sediments	
		80.120 mg/kg	Soil	
		0.072 mg/l	Intermittent releases (freshwater)	

1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	1065336-91-5	2.200 µg/l	Freshwater
		9.000 µg/l	Intermittent releases (freshwater)
		220.000 ng/L	Marine water
		1.000 mg/l	Microorganisms in sewage treatments
		1.050 mg/kg	Freshwater sediments
		110.000 µg/kg	Marine water sediments
		210.000 µg/kg	Soil

Derived No Effect Level (DNEL) values

Component	CAS-No.	Worker Industry	Worker Professional	Consumer	Exposure Route	Exposure Frequency
bis-[4-(2,3-epoxipropoxy)phenyl] propane	1675-54-3		0.750 mg/kg		Human Oral	Long Term, local effects
			0.750 mg/kg		Human Oral	Long Term, systemic effects
			3.571 mg/kg		Human Dermal	Long Term, systemic effects
			3.571 mg/kg		Human Dermal	Long Term, local effects
			12.250 mg/m ³		Human Inhalation	Long Term, systemic effects
			12.250 mg/m ³		Human Inhalation	Long Term, local effects
titanium dioxide	13463-67-7		10.000 mg/m ³		Human Inhalation	Long Term, local effects
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2		17.000 mg/kg	10.000 mg/kg	Human Dermal	Short Term, systemic effects
			29.000 mg/m ³	7.600 mg/m ³	Human Inhalation	Short Term, systemic effects
				1219.000 mg/kg	Human Oral	Short Term, systemic effects
			68.000 mg/kg	40.000 mg/kg	Human Dermal	Short Term, local effects
			9.800 mg/m ³	2.900 mg/m ³	Human Inhalation	Short Term, local effects
			3.900 mg/kg	2.350 mg/kg	Human Dermal	Long Term, systemic effects
			13.800 mg/m ³	4.100 mg/m ³	Human Inhalation	Long Term, systemic effects
				1.000 mg/kg	Human Oral	Long Term, systemic effects
			1.700 mg/kg	1.000 mg/kg	Human Dermal	Long Term, local effects
			0.980 mg/kg	1.460 mg/kg	Human Inhalation	Long Term, local effects
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-	1065336-91-5		680.000 µg/m ³	170.000 µg/m ³	Human Inhalation	Long Term, systemic effects

pentamethylpiperidin-4-yl) decanedioate

500.000 µg/kg	250.000 µg/kg	Human Dermal	Long Term, systemic effects
	50.000 µg/kg	Human Oral	Long Term, systemic effects

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.

Protection for skin:

Disposable suit.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

N.A.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Solid

Color: In compliance with the product description

Odour: Characteristic

Odour threshold: N.A.

pH: Not Relevant

Kinematic viscosity: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: > 200 °C (392 °F)

Flash point: Not Applicable

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 1.68 g/cm³

Solubility in water: Insoluble

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Flammability: N.A.

Volatile Organic compounds - VOCs = 0 % ; 0 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

Miscibility: N.A.

Conductivity: N.A.

Evaporation rate: N.A. No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1B(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

bis-[4-(2,3-epoxipropoxy)phenyl]propane	a) acute toxicity	LD50 Oral Rabbit = 19800.00000 mg/kg	
		LD50 Skin Rabbit > 20.00000 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive	epoxy resin with an average molecular mass ≤ 700 d irritate skin of rabbits
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
	f) carcinogenicity	Genotoxicity Negative	Mouse, oral
		Carcinogenicity Oral Rat = 15.00000 mg/kg	NOAEL
		Carcinogenicity Skin Rat = 1.00000 mg/kg	NOAEL
	g) reproductive toxicity	No Observed Effect Level Oral Rat = 750.00000 mg/kg	
titanium dioxide	a) acute toxicity	LD50 Oral Rat > 5000.00 mg/kg	
		LC50 Inhalation > 6.82 mg/l	
	d) respiratory or skin sensitisation	Skin Sensitization Negative	
	i) STOT-repeated exposure	No Observed Adverse Effect Level 1000.00	
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	a) acute toxicity	LD50 Oral Rat = 26800.00000 mg/kg	
		LC50 Inhalation Rat > 0.20600 mg/l 4h	
		LD50 Skin Rabbit > 4.50000 ml/Kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Yes	

	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Guinea pig Positive	
	g) reproductive toxicity	No Observed Adverse Effect Level Skin Rat = 200.00000 mg/kg	
Alcohols, C12-15, branched and linear, ethoxylated	a) acute toxicity	LD50 Oral > 300.00 mg/kg	
Quartz	a) acute toxicity	LD50 Oral > 2000.00000 mg/kg	
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	a) acute toxicity	LD50 Oral Rat = 3230.00 mg/kg	
		LD50 Skin Rat > 3170.00 mg/kg	
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative 24h	
	c) serious eye damage/irritation	Eye Irritant Rabbit No	
	d) respiratory or skin sensitisation	Skin Sensitization Guinea pig Positive	
	f) carcinogenicity	Genotoxicity Negative	Mouse oral route
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 30.00 mg/kg	

11.2 Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Harmful to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS: 1675-54-3 - EINECS: 216-823-5 - INDEX: 603-073-00-2	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 2.00000 mg/L 96h a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 1.80000 mg/L 48h a) Aquatic acute toxicity : EC50 Algae Scenedesmus capricornutum = 11.00000 mg/L 72h EPA-660/3-75-009 c) Bacteria toxicity : EC50 Sludge activated sludge = 100.00000 mg/L 96h
titanium dioxide	CAS: 13463-67-7 - EINECS: 236-675-5 - INDEX: 022-006-00-2	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas (Cavedano americano) > 1000.00 mg/L 96h a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata (alghe cloroficee) > 100.00 mg/L 72h

		a) Aquatic acute toxicity : NOEC Algae = 5600.00 mg/L
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna (Pulce d'acqua grande) > 100.00 mg/L 48h
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS: 68609-97-2 - EINECS: 271-846-8 - INDEX: 603-103-00-4	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss > 5000.00000 mg/L 96h
		a) Aquatic acute toxicity : NOEC Algae Pseudokirchneriella subcapitata = 500.00000 mg/L 72h ,,OECD Guideline 201 (Alga, Growth Inhibition Test)
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 843.00000 mg/L 72h
		c) Bacteria toxicity : EC50 Sludge > 100.00000 mg/L
Alcohols, C12-15, branched and linear, ethoxylated	CAS: 106232-83-1	a) Aquatic acute toxicity : LC50 Fish Carassius Auratus < 10.00 mg/L 96h CESIO
		a) Aquatic acute toxicity : EC50 Honeybees Daphnie < 10.00 mg/L 48h CESIO
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	CAS: 1065336-91-5 - EINECS: 915-687-0	a) Aquatic acute toxicity : LC50 Fish Danio rerio = 0.90 mg/L 96h OECD Guideline 203
		b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 1.00 mg/L OECD guideline 211
		a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 1.68 mg/L 72h OECD Guideline 201
		a) Aquatic acute toxicity : EC20 Sludge activated sludge >= 100.00 mg/L 3h OECD guideline 209

12.2. Persistence and degradability

Component	Persistence/Degradability	Test	Duration	Value	Notes
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Non-readily biodegradable	Oxygen consumption			OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Readily biodegradable	Oxygen consumption		87.000	%; OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Alcohols, C12-15, branched and linear, ethoxylated	Readily biodegradable		28d		>70% (OECD tg 301 B)
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	Non-readily biodegradable			38.000	28days

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Bioaccumulative	BCF - Bioconcentration factor	31.000
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Bioaccumulative	BCF - Bioconcentration factor	160.000
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	Not bioaccumulative		

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7 Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

A waste code according to European waste catalogue (EWC) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

HP 13: Sensitising; HP 4: Irritant — skin irritation and eye damage; HP 14: Ecotoxic

SECTION 14: Transport information

14.1. UN number or ID number

N/A

14.2. UN proper shipping name

ADR-Shipping Name: N/A

IATA-Technical name: N/A

IMDG-Technical name: N/A

14.3. Transport hazard class(es)

ADR-Class: N/A

IATA-Class: N/A

IMDG-Class: N/A

14.4. Packing group

ADR-Packing Group: N/A

IATA-Packing group: N/A

IMDG-Packing group: N/A

14.5. Environmental hazards

Marine pollutant: No

Environmental Pollutant: No

IMDG-EMS: N/A

14.6. Special precautions for user

Road and Rail (ADR-RID) :

ADR-Label: N/A

ADR - Hazard identification number: N/A

ADR-Special Provisions: N/A

ADR-Transport category (Tunnel restriction code): N/A

ADR Limited Quantities: N/A

ADR Excepted Quantities: N/A

Air (IATA) :

IATA-Passenger Aircraft: N/A

IATA-Cargo Aircraft: N/A

IATA-Label: N/A

IATA-Subsidiary hazards: N/A

IATA-Erg: N/A

IATA-Special Provisioning: N/A

Sea (IMDG) :

IMDG-Stowage Code: N/A

IMDG-Stowage Note: N/A

IMDG-Subsidiary hazards: N/A

IMDG-Special Provisioning: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)
 Regulation (EC) n. 1272/2008 (CLP)
 Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
 Regulation (EU) n. 286/2011 (ATP 2 CLP)
 Regulation (EU) n. 618/2012 (ATP 3 CLP)
 Regulation (EU) n. 487/2013 (ATP 4 CLP)
 Regulation (EU) n. 944/2013 (ATP 5 CLP)
 Regulation (EU) n. 605/2014 (ATP 6 CLP)
 Regulation (EU) n. 2015/1221 (ATP 7 CLP)
 Regulation (EU) n. 2016/918 (ATP 8 CLP)
 Regulation (EU) n. 2016/1179 (ATP 9 CLP)
 Regulation (EU) n. 2017/776 (ATP 10 CLP)
 Regulation (EU) n. 2018/669 (ATP 11 CLP)
 Regulation (EU) n. 2018/1480 (ATP 13 CLP)
 Regulation (EU) n. 2019/521 (ATP 12 CLP)
 Regulation (EU) n. 2020/217 (ATP 14 CLP)
 Regulation (EU) n. 2020/1182 (ATP 15 CLP)
 Regulation (EU) n. 2021/643 (ATP 16 CLP)
 Regulation (EU) n. 2020/878
 Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: None

Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

Regulation (EU) 649/2012 (PIC regulation):

No Substance Listed

German Water Hazard Class.

Class 1: slightly hazardous for water.

SVHC Substances:

No data available

15.2. Chemical safety assessment

A Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
EUH212	Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A

3.4.2/1B	Skin Sens. 1B	Skin Sensitisation, Category 1B
3.7/2	Repr. 2	Reproductive toxicity, Category 2
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category 1
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008 Classification procedure

3.2/2	Calculation method
3.3/2	Calculation method
3.4.2/1B	Calculation method
4.1/C3	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

- ACGIH: American Conference of Governmental Industrial Hygienists
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- ATE: Acute Toxicity Estimate
- ATEmix: Acute toxicity Estimate (Mixtures)
- BCF: Biological Concentration Factor
- BEI: Biological Exposure Index
- BOD: Biochemical Oxygen Demand
- CAS: Chemical Abstracts Service (division of the American Chemical Society).
- CAV: Poison Center
- CE: European Community
- CLP: Classification, Labeling, Packaging.
- CMR: Carcinogenic, Mutagenic and Reprotoxic
- COD: Chemical Oxygen Demand
- COV: Volatile Organic Compound
- CSA: Chemical Safety Assessment
- CSR: Chemical Safety Report
- DMEL: Derived Minimal Effect Level
- DNEL: Derived No Effect Level.
- DPD: Dangerous Preparations Directive
- DSD: Dangerous Substances Directive
- EC50: Half Maximal Effective Concentration
- ECHA: European Chemicals Agency
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ES: Exposure Scenario
- GefStoffVO: Ordinance on Hazardous Substances, Germany.
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
- IARC: International Agency for Research on Cancer
- IATA: International Air Transport Association.
- IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
- IC50: half maximal inhibitory concentration
- ICAO: International Civil Aviation Organization.
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
- IMDG: International Maritime Code for Dangerous Goods.
- INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care
KAFH: Keep Away From Heat
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LDLo: Leathal Dose Low
N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration.
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 12. ECOLOGICAL INFORMATION
- 16. OTHER INFORMATION

Exposure Scenario

1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate

Exposure Scenario, 20/04/2022

Substance identity	
	1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate
CAS No.	1065336-91-5
EINECS No.	915-687-0

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9a, PC9b)

1. ES 1

Widespread use by professional workers; Various products (PC9a, PC9b)

1.1 TITLE SECTION

Exposure Scenario name	Professional application of coatings and inks - Use in rigid foams, coatings, adhesives and sealants
Date - Version	20/04/2022 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Coatings and paints, thinners, paint removers (PC9a) - Fillers, putties, plasters, modelling clay (PC9b)

Environment Contributing Scenario

CS1 ERC8c

Worker Contributing Scenario

CS2 Material transfers PROC8a

CS3 Rolling, Brushing PROC10

1.2 Conditions of use affecting exposure**1.2. CS1: Environment Contributing Scenario (ERC8c)**

Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) (ERC8c)
---	--

*Product (article) characteristics***Physical form of product:**

Liquid

Vapour pressure:

Vapour pressure < 0.01 Pa at standard temperature and pressure 0.0001 Pa

*Amount used, frequency and duration of use (or from service life)***Emission days:** 365 days per year*Technical and organisational conditions and measures***Control measures to prevent releases**

Air - minimum efficiency of: 15 % Water - minimum efficiency of: 1 %

*Conditions and measures related to sewage treatment plant***STP type:**

Municipal Sewage Treatment Plant

Water - minimum efficiency of: = 88.9 %

STP effluent (m³/day): 2000*Other conditions affecting environmental exposure***Local marine water dilution factor:** 100**Local freshwater dilution factor:** 10**Receiving surface water flow:** 18000 m³/day

Indoor use

1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
Product (article) characteristics	
Physical form of product: Liquid	
Vapour pressure: Vapour pressure < 0.01 Pa at standard temperature and pressure 0.0001 Pa	
Concentration of substance in product: Covers percentage substance in the product up to 5 %.	
Amount used, frequency and duration of use/exposure	
Duration: Covers use up to 480 min	
Frequency: Covers use up to 5 days per week	
Technical and organisational conditions and measures	
Technical and organisational measures Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed. Ensure operatives are trained to minimise exposures.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection	
Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.	Dermal - minimum efficiency of: = 90 %
Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin.	
Other conditions affecting worker exposure	
Indoor use Professional use	
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.	
Additional Good Practice Advice: Ensure no splashing occurs during transfer.	
1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)	
Process Categories	Roller application or brushing (PROC10)
Product (article) characteristics	
Physical form of product: Liquid	
Vapour pressure: Vapour pressure < 0.01 Pa at standard temperature and pressure 0.0001 Pa	
Concentration of substance in product: Covers percentage substance in the product up to 5 %.	
Amount used, frequency and duration of use/exposure	
Duration: Covers use up to 480 min	
Frequency: Covers use up to 5 days per week	
Technical and organisational conditions and measures	
Technical and organisational measures	

Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed. Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.	Dermal - minimum efficiency of: = 90 %
Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin.	

Other conditions affecting worker exposure

Indoor use
Professional use

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Ensure no splashing occurs during transfer.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8c)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
soil	N/A	ECETOC TRA environment v2.0	0.0579

Additional information on exposure estimation:

Risk from environmental exposure is driven by soil.

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 0.2743 mg/kg bw/day	ECETOC TRA worker v3	= 0.137143
inhalative, systemic, long-term	= 0.4233 mg/m ³	ECETOC TRA worker v3	= 0.119924

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 0.5486 mg/kg bw/day	ECETOC TRA worker v3	= 0.274286
inhalative, systemic, long-term	= 0.274286 mg/m ³	ECETOC TRA worker v3	= 0.097

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Exposure Scenario, 07/06/2021

Substance identity	
	bis-[4-(2,3-epoxipropoxy)phenyl]propane
CAS No.	1675-54-3
INDEX No.	603-073-00-2
EINECS No.	216-823-5
Registration number	01-2119456619-26

Table of contents

1. **ES 1** Widespread use by professional workers; ESC2_0000001

1. ES 1 Widespread use by professional workers; ESC2_0000001

1.1 TITLE SECTION

Exposure Scenario name	Professional application of coatings and inks - Etching agent - Resins (prepolymers) - Adhesion promotor
Date - Version	27/05/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	ESC2_0000001
Article Category(ies)	Other articles made of stone, plaster, cement, glass or ceramic (AC4g)

Environment Contributing Scenario

CS1	ERC8c - ERC8f
-----	---------------

Worker Contributing Scenario

CS2 Material transfers	PROC8a
CS3 Rolling, Brushing	PROC10
CS4 Roller, spreader, flow application	PROC11
CS5 Mixing operations - Manual	PROC19

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)

Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use (or from service life)

Amounts used:

Daily amount per site = 175 kg/day

Release type: Continuous release

Emission days: 365 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Provide onsite wastewater removal efficiency of ³ (%):

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant

STP effluent (m³/day): 2

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Dispose of waste cans and containers according to local regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Receiving surface water flow: 18000 m³/day

Covers indoor and outdoor use

1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories

Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories

Roller application or brushing (PROC10)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories

Non industrial spraying (PROC11)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Wear suitable face shield.

Wear an impervious suit.

Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS5: Worker Contributing Scenario: Mixing operations - Manual (PROC19)**Process Categories**

Manual activities involving hand contact (PROC19)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 1 hour per day.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source**1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)**

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	= 0.0022 mg/L	EUSES	= 0.00022
marine sediment	= 0.00127 mg/L	EUSES	= 0.0128
freshwater sediment	= 0.012 mg/L	EUSES	= 0.0369
marine water	= 2.34E-05 mg/L	EUSES	= 0.029
soil	= 0.00142 mg/kg dry weight	EUSES	= 0.00722

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 0.84 mg/m ³	ECETOC TRA worker v2.0	0.07
dermal, systemic, long-term	= 0.2742 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.03

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 5E-07 mg/m ³	ECETOC TRA worker v2.0	< 0.001
dermal, systemic, long-term	= 2.743 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.33

1.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 0.36 mg/m ³	ECETOC TRA worker v2.0	0.03
dermal, systemic, long-term	= 2.68 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.32

1.3. CS5: Worker Contributing Scenario: Mixing operations - Manual (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 2E-07 mg/m ³	ECETOC TRA worker v2.0	< 0.001
dermal, systemic, long-term	= 1.414 mg/kg bw/day	ECETOC TRA worker v3	< 0.42
combined routes, systemic, long-term	N/A	ECETOC TRA worker v3	= 0.42

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario

oxirane, mono[(c12-14-alkyloxy)methyl] derivs.

Exposure Scenario, 08/06/2021

Substance identity	
	oxirane, mono[(c12-14-alkyloxy)methyl] derivs.
CAS No.	68609-97-2
INDEX No.	603-103-00-4
EINECS No.	271-846-8
Registration number	01-2119485289-22

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC1, PC9a, PC9b)

1. ES 1

Widespread use by professional workers; Various products (PC1, PC9a, PC9b)

1.1 TITLE SECTION

Exposure Scenario name	Professional application of coatings and inks by brush or roller - Professional application of coatings and inks
Date - Version	07/04/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Adhesives, sealants (PC1) - Coatings and paints, thinners, paint removers (PC9a) - Fillers, putties, plasters, modelling clay (PC9b)

Environment Contributing Scenario

CS1	ERC8c
------------	-------

Worker Contributing Scenario

CS2 Mixing operations	PROC5
CS3 Large surfaces - Surfaces - Rolling, Brushing	PROC10
CS4 Large surfaces - Surfaces - Roller, spreader, flow application	PROC11
CS5 Large surfaces - Surfaces - Rolling, Brushing	PROC19

1.2 Conditions of use affecting exposure**1.2. CS1: Environment Contributing Scenario (ERC8c)**

Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) (ERC8c)
---	--

*Product (article) characteristics***Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

*Amount used, frequency and duration of use (or from service life)***Release type:** Intermittent release**1.2. CS2: Worker Contributing Scenario: Mixing operations (PROC5)**

Process Categories	Mixing or blending in batch processes (PROC5)
---------------------------	---

*Product (article) characteristics***Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 25 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

*Technical and organisational conditions and measures***Technical and organisational measures**

Ensure operatives are trained to minimise exposures.

Avoid direct eye contact with product, also via contamination on hands.

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Wear suitable gloves tested to EN374.

<i>Other conditions affecting worker exposure</i>	
Indoor use Professional use Temperature: Covers use at ambient temperatures. Body parts exposed: Assumes that potential dermal contact is limited to hands and forearms.	
1.2. CS3: Worker Contributing Scenario: Large surfaces - Surfaces - Rolling, Brushing (PROC10)	
Process Categories	Roller application or brushing (PROC10)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP	
Concentration of substance in product: Covers percentage substance in the product up to 25 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Ensure operatives are trained to minimise exposures. Provide extract ventilation to points where emissions occur. Avoid direct eye contact with product, also via contamination on hands. Use long handled brushes and rollers.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140.	
<i>Other conditions affecting worker exposure</i>	
Indoor use Professional use Temperature: Covers use at ambient temperatures.	
1.2. CS4: Worker Contributing Scenario: Large surfaces - Surfaces - Roller, spreader, flow application (PROC11)	
Process Categories	Non industrial spraying (PROC11)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
Frequency: For each use, avoid using for more than < 4 h/event	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Ensure operatives are trained to minimise exposures. Provide extract ventilation to points where emissions occur. Avoid direct eye contact with product, also via contamination on hands. Use long handled brushes and rollers. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	

Personal protection

Wear suitable gloves tested to EN374.
Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Indoor use
Professional use

Temperature: Covers use at ambient temperatures.

1.2. CS5: Worker Contributing Scenario: Large surfaces - Surfaces - Rolling, Brushing (PROC19)**Process Categories**

Manual activities involving hand contact (PROC19)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 25 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Frequency:

For each use, avoid using for more than < 1 h/event

Technical and organisational conditions and measures**Technical and organisational measures**

Ensure operatives are trained to minimise exposures.
Provide extract ventilation to points where emissions occur.
Avoid direct eye contact with product, also via contamination on hands.
Use long handled brushes and rollers.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use
Professional use

Temperature: Covers use at ambient temperatures.

1.3 Exposure estimation and reference to its source**1.3. CS2: Worker Contributing Scenario: Mixing operations (PROC5)**

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 9.3 mg/m ³	ECETOC TRA worker v2.0	= 0.674
dermal, systemic, long-term	= 0.007 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.002

Additional information on exposure estimation:

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374.

1.3. CS3: Worker Contributing Scenario: Large surfaces - Surfaces - Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
---	----------------	--------------------	-----------------------------------

inhalative, local, short-term	= 2.325 mg/m ³	ECETOC TRA worker v2.0	= 0.168
dermal, systemic, long-term	= 0.137 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.035

Additional information on exposure estimation:

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374.

1.3. CS4: Worker Contributing Scenario: Large surfaces - Surfaces - Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, local, short-term	= 0.36 mg/m ³	ECETOC TRA worker v2.0	= 0.03
dermal, systemic, long-term	= 2.68 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.32

Additional information on exposure estimation:

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374.

1.3. CS5: Worker Contributing Scenario: Large surfaces - Surfaces - Rolling, Brushing (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, local, long-term	= 2E-07 mg/m ³	ECETOC TRA worker v2.0	< 0.001
dermal, systemic, long-term	= 1.414 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.42

Additional information on exposure estimation:

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374.

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

FUGALITE BIO (B)

Date of first edition: 11/28/2022

Safety Data Sheet dated 11/28/2022

version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: FUGALITE BIO (B)

Trade code: B0046 .091

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: hardener

Uses advised against: Data not available.

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel.+39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Kerakoll Italy - +39-0536-816511

Ireland

Poison information centre: 01 809 2166 (Daily 8am-10pm)

In case of emergency call 999 or 112

Malta

In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1A May cause an allergic skin reaction.

Aquatic Chronic 3 Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Pictograms and Signal Words



Danger

Hazard statements

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P280 Wear protective gloves and eye protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501 Dispose of contents/container in accordance with applicable regulations.

Contains

Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction

Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

PHENOL, 4,4-(1-METHYLETHYLIDENE)BIS-, POLYMER WITH N-(2-AMINOETHYL)-1,2-ETHANEDIAMINE,(CHLOROMETHYL)OXIRANE, ALPHA-HYDRO-OMEGA-HYDROXYPOLY[OXY(METHYL-1,2-ETHANEDIYL)] ETHER WITH2,2-BIS(HYDROXYMETHYL)-1,3-PROPANEDIOL (4:1) OXIRANYLMETHYL ETHER, AND ME

Alcohols, C12-15, branched and linear, ethoxylated

3,6,9,12-tetra-azatetradecamethylenediamine; pentachthylenhexamine

Amines, polyethylenepoly-, triethylenetetramine fraction

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%.

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: FUGALITE BIO (B)

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
10-19,9 %	PHENOL, 4,4-(1-METHYLETHYLIDENE)BIS-, POLYMER WITH N-(2-AMINOETHYL)-1,2-ETHANEDIAMINE, (CHLOROMETHYL)OXIRANE, ALPHA-HYDRO-OMEGA-HYDROXYPOLY[OXY(METHYL-1,2-ETHANEDIYL)] ETHER WITH2,2-BIS(HYDROXYMETHYL)-1,3-PROPANEDIOL (4:1) OXIRANYLMETHYL ETHER, AND ME	CAS:455946-46-0	Eye Dam. 1, H318	
1-2,4 %	Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	CAS:68082-29-1 EC:500-191-5	Skin Irrit. 2, H315; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Sens. 1A, H317, M-Chronic:1	01-2119972320-44
1-2,4 %	Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction	EC:701-046-0	Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1A, H317; Aquatic Chronic 2, H411, M-Chronic:1	01-2119972321-42
1-2,4 %	Alcohols, C12-15, branched and linear, ethoxylated	CAS:106232-83-1	Acute Tox. 4, H302; Eye Dam. 1, H318; Aquatic Chronic 3, H412	
< 1 %	Amines, polyethylenepoly-, tetraethylenepentamine fraction	CAS:90640-66-7 EC:292-587-7	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Corr. 1B, H314; Skin Sens. 1,1A,1B, H317; Eye Dam. 1, H318; Aquatic Chronic 2, H411	01-2119487290-37
< 1 %	POLYETHYLENE POLYAMINE, PENTAETHYLENEHEXAMINE FRACTION	EC:701-266-7	Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Eye Dam. 1, H318;	01-2119485826-22

			Aquatic Acute 1, H400; Aquatic Chronic 1, H410, EUH071
< 0,5 %	Quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372
< 0,5 %	titanium dioxide	CAS:13463-67-7 EC:236-675-5 Index:022-006-00-2	EUH212
< 0,5 %	Amines, polyethylenepoly-, triethylenetetramine fraction	CAS:90640-67-8 EC:292-588-2 Index:612-059-00-5	Acute Tox. 4, H312; Acute Tox. 4, 01-2119487919-13 H302; Skin Corr. 1B, H314; Eye Dam. 1, H318; Skin Sens. 1, H317; Aquatic Chronic 3, H412

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

- None in particular.

5.2. Special hazards arising from the substance or mixture

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.

5.3. Advice for firefighters

- Use suitable breathing apparatus .
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- Wear personal protection equipment.
- Remove persons to safety.
- See protective measures under point 7 and 8.

6.2. Environmental precautions

- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Retain contaminated washing water and dispose it.
- In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
- Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

- Suitable material for taking up: absorbing material, organic, sand
- Wash with plenty of water.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
 Don't use empty container before they have been cleaned.
 Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
 Contaminated clothing should be changed before entering eating areas.
 Do not eat or drink while working.
 See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:
 None in particular.
 Instructions as regards storage premises:
 Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)
 None in particular
 Industrial sector specific solutions:
 None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

Component	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Notes
Quartz	NATIONAL	AUSTRALIA		0.100				Respirable fraction
	NATIONAL	AUSTRIA		0.150				Respirable aerosol
	NATIONAL	BELGIUM		0.100				
	NATIONAL	CANADA		0.100				Canada Ontario; Respirable aerosol
	NATIONAL	CANADA		0.100				Canada Quebec
	NATIONAL	DENMARK		0.300		0.600		Inhalable aerosol
	NATIONAL	DENMARK		0.100		0.200		Respirable aerosol
	NATIONAL	FINLAND		0.050				Respirable fraction
	NATIONAL	FRANCE		0.100				Respirable aerosol
	NATIONAL	HUNGARY		0.150				Respirable aerosol
	NATIONAL	IRELAND		0.100				Respirable fraction
	NATIONAL	NEW ZEALAND		0.200				Respirable aerosol
	NATIONAL	CHINA		1.000				Inhalable fraction. 10% <= free SiO2 <= 50%.
	NATIONAL	CHINA		0.700				Inhalable fraction. 50% < free SiO2 <= 80%.
	NATIONAL	CHINA		0.500				Inhalable fraction. Free SiO2 < 80%.
	NATIONAL	SINGAPORE		0.100				Respirable aerosol.
	NATIONAL	SPAIN		0.100				Respirable fraction
	NATIONAL	SWEDEN		0.100				Respirable aerosol
	NATIONAL	SWITZERLAND		0.150				Respirable aerosol
	NATIONAL	NETHERLANDS		0.075				Respirable dust
NATIONAL	ITALY		0.050				Silice cristallina	
NATIONAL	ITALY		0.025				A2	

	NATIONAL	ITALY	10.000		Come particelle non altrimenti specificate PNOC
	NATIONAL	KOREA, REPUBLIC OF	0.050		
	NATIONAL	UNITED STATES OF AMERICA	0.050		NIOSH
	NATIONAL	ARGENTINA	0.050		
	NATIONAL	CHILE	0.080		
	NATIONAL	CROATIA	0.100		
	NATIONAL	ESTONIA	0.100		
	NATIONAL	INDIA	10.000		
	NATIONAL	LITHUANIA	0.100		
	NATIONAL	MALAYSIA	0.100		
	NATIONAL	MEXICO	0.025		Respirable fraction
	NATIONAL	NORWAY	0.300		Total dust
	NATIONAL	NORWAY	0.100		Respirable dust
	NATIONAL	POLAND	0.100		Respirable fraction
	NATIONAL	PORTUGAL	0.025		Respirable fraction
	NATIONAL	SLOVENIA	0.050	0.400	
	NATIONAL	SOUTH AFRICA	0.100		
	ACGIH	NNN	0.025		(R), A2 - Pulm fibrosis, lung cancer
Calcium carbonate	NATIONAL	AUSTRALIA	10.000		This value is for inhalable dust containing no asbestos and <1 % crystalline silica.
	NATIONAL	CANADA	10.000		
	NATIONAL	FRANCE	10.000		inhalable aerosol
	NATIONAL	HUNGARY	10.000		inhalable aerosol
	NATIONAL	IRELAND	10.000		Inhalable fraction
	NATIONAL	IRELAND	4.000		Respirable fraction
	NATIONAL	LATVIA	6.000		
	NATIONAL	NEW ZEALAND	10.000		The value for inhalable dust containing no asbestos and less than 1% free silica.
	NATIONAL	POLAND	10.000		
	NATIONAL	SINGAPORE	10.000		(limestone, marble)
	NATIONAL	SWITZERLAND	3.000		respirable aerosol
	NATIONAL	UNITED STATES OF AMERICA	15.000		total dust
	NATIONAL	UNITED STATES OF AMERICA	5.000		respirable dust
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	10.000		inhalable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND	4.000		respirable aerosol

		NORTHERN IRELAND					
	NATIONAL	ITALY	10.000				
	NATIONAL	BELGIUM	10.000				
	NATIONAL	KOREA, REPUBLIC OF	10.000				
	NATIONAL	CROATIA	10.000				
	NATIONAL	NETHERLANDS	10.000				
	NATIONAL	PORTUGAL	10.000				
	NATIONAL	SPAIN	10.000				
	NATIONAL	CHILE	5.000				respirable fraction
benzyl alcohol	NATIONAL	FINLAND	45.000	10.000			
	NATIONAL	GERMANY	22.000	5.000	44.000	10.000	AGS; Long term and short term: inhalable fraction
	NATIONAL	GERMANY	22.000	5.000	44.000	10.000	DFG; Long term and short term: inhalable fraction
	NATIONAL	LATVIA	5.000				
	NATIONAL	SWITZERLAND	5.000	22.000			
	NATIONAL	BULGARIA	5.000				
	NATIONAL	CZECHIA	40.000		80.000		
	NATIONAL	LITHUANIA	5.000				
	NATIONAL	POLAND	240.000				
	NATIONAL	RUSSIAN FEDERATION				5.000	
	NATIONAL	SLOVENIA	22.000	5.000	44.000	10.000	
	NATIONAL	UNITED STATES OF AMERICA		10.000			
Quartz	NATIONAL	AUSTRALIA	0.100				Respirable fraction
	NATIONAL	AUSTRIA	0.150				respirable aerosol
	NATIONAL	BELGIUM	0.100				
	NATIONAL	CANADA	0.100				Canada Ontario. Respirable aerosol
	NATIONAL	CANADA	0.100				Canada Quebec
	NATIONAL	DENMARK	0.300		0.600		Inhalable aerosol
	NATIONAL	DENMARK	0.100		0.200		Respirable aerosol
	NATIONAL	FINLAND	0.050				Respirable fraction
	NATIONAL	FRANCE	0.100				Respirable aerosol
	NATIONAL	HUNGARY	0.150				Respirable aerosol
	NATIONAL	IRELAND	0.100				Respirable fraction
	NATIONAL	NEW ZEALAND	0.200				Respirable aerosol
	NATIONAL	CHINA	1.000				Inhalable fraction. 10% <= free SiO2 <= 50%.
	NATIONAL	CHINA	0.700				Inhalable fraction. 50% < free SiO2 <= 80%.
	NATIONAL	CHINA	0.500				Inhalable fraction. Free SiO2 < 80%.
	NATIONAL	SINGAPORE	0.100				Respirable aerosol.
	NATIONAL	SPAIN	0.100				Respirable fraction
	NATIONAL	SWEDEN	0.100				Respirable aerosol

	NATIONAL	SWITZERLAND	0.150		Respirable aerosol
	NATIONAL	NETHERLANDS	0.075		Respirable dust
	NATIONAL	ITALY	0.050		Silice cristallina
	NATIONAL	ITALY	0.025		A2
	NATIONAL	UNITED STATES OF AMERICA	0.050		NIOSH
	NATIONAL	KOREA, REPUBLIC OF	0.050		
	NATIONAL	ARGENTINA	0.050		
	NATIONAL	CHILE	0.080		
	NATIONAL	CROATIA	0.100		
	NATIONAL	ESTONIA	0.100		
	NATIONAL	INDIA	10.000		
	NATIONAL	LITHUANIA	0.100		
	NATIONAL	MALAYSIA	0.100		
	NATIONAL	MEXICO	0.025		Respirable fraction
	NATIONAL	NORWAY	0.300		Total dust
	NATIONAL	NORWAY	0.100		Respirable dust
	NATIONAL	POLAND	0.100		Respirable fraction
	NATIONAL	PORTUGAL	0.025		
	NATIONAL	SLOVENIA	0.050	0.400	
	NATIONAL	SOUTH AFRICA	0.100		
	ACGIH	NNN	0.025		(R), A2 - Pulm fibrosis, lung cancer
	EU	NNN	0.100		(R), A2 - Pulm fibrosis, lung cancer
titanium dioxide	NATIONAL	AUSTRALIA	10		
	NATIONAL	BELGIUM	10.000		
	NATIONAL	CANADA	10.000		Ontario
	NATIONAL	CANADA	10.000		Quebec
	NATIONAL	DENMARK	6.000	12.000	Long term and short term: total dust
	NATIONAL	FRANCE	11.000		Inhalable aerosol
	NATIONAL	GERMANY	0.300	2.400	DFG; Long term and short term: excluding ultrafine particles; respirable fraction; multiplied by the material density;
	NATIONAL	IRELAND	10.000		Inhalable fraction
	NATIONAL	IRELAND	8.000		Respirable fraction
	NATIONAL	JAPAN	0.300		JSOH; Nanoparticle, as Ti
	NATIONAL	LATVIA	10.000		
	NATIONAL	NEW ZEALAND	10000.000		The value for inhalable dust containing no asbestos and less than 1% free silica
	NATIONAL	CHINA	8.000		Inhalable fraction
	NATIONAL	POLAND	10.000	30.000	
	NATIONAL	ROMANIA	10.000	15.000	
	NATIONAL	SINGAPORE	10.000		
	NATIONAL	KOREA, REPUBLIC	10.000		

		OF			
silicon dioxide, chemically prepared	NATIONAL	SPAIN	10.000		Inhalable aerosol
	NATIONAL	SWEDEN	5.000		Inhalable aerosol
	NATIONAL	SWITZERLAND	3.000		Respirable aerosol
	NATIONAL	UNITED STATES OF AMERICA	15.000		OSHA; total dust
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	10.000		Inhalable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	4.000		Respirable aerosol
	NATIONAL	ITALY	10.000		
	NATIONAL	ARGENTINA	10.000		
	NATIONAL	AUSTRIA	5.000	10.000	
	NATIONAL	BULGARIA	10.000		
	NATIONAL	CROATIA	10.000		total dust
	NATIONAL	CROATIA	4.000		respirable dust
	NATIONAL	GREECE	10.000		
	NATIONAL	GREECE	50.000		
	NATIONAL	GREECE	5.000		
	NATIONAL	INDONESIA	10.000		
	NATIONAL	LITHUANIA	5.000		
	NATIONAL	MALAYSIA	10.000		
	NATIONAL	MEXICO	10.000		
	NATIONAL	NORWAY	5.000		
	NATIONAL	PORTUGAL	10.000		
	NATIONAL	RUSSIAN FEDERATION	10.000		
	NATIONAL	SLOVAKIA	5.000		
	NATIONAL	SLOVENIA	6.000		
	NATIONAL	SOUTH SUDAN	10.000		Inhalable fraction
	NATIONAL	SOUTH SUDAN	5.000		Respirable fraction
	NATIONAL	TAIWAN, PROVINCE OF CHINA	10.000		
ACGIH	NNN	10.000		A4 - LRT irr	
NATIONAL	AUSTRALIA	2.000		This value is for inhalable dust containing no asbestos and < 1% crystalline silica	
NATIONAL	AUSTRIA	4.000		Inhalable aerosol	
NATIONAL	BELGIUM	10.000			
NATIONAL	CANADA	10.000		Ontario	
NATIONAL	CANADA	6.000		Quebec	
NATIONAL	DENMARK	2.000	4.000	Inhalable aerosol	

	NATIONAL	FINLAND	5.000		
	NATIONAL	GERMANY	4.000		AGS; Inhalable aerosol
	NATIONAL	GERMANY	4.000		DFG; Inhalable aerosol
	NATIONAL	IRELAND	6.000		Inhalable fraction
	NATIONAL	IRELAND	2.400		Respirable fraction
	NATIONAL	LATVIA	1.000		
	NATIONAL	NEW ZEALAND	1.000		
	NATIONAL	CHINA	2.000		Inhalable fraction
	NATIONAL	SINGAPORE	10.000		
	NATIONAL	KOREA, REPUBLIC OF	10.000		
	NATIONAL	SWITZERLAND	4.000		Inhalable aerosol
	NATIONAL	UNITED STATES OF AMERICA	80.000		OSHA; 80/ % silica total dust (MG3)
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	6.000		Inhalable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	2.400		Respirable aerosol
	NATIONAL	ESTONIA	2.000		
	NATIONAL	SLOVENIA	4.000		Inhalable fraction
	NATIONAL	SOUTH AFRICA	6.000		Inhalable particulate
	NATIONAL	SOUTH AFRICA	3.000		Respirable particulate
Aluminium oxide	NATIONAL	FRANCE	10.000		Respirable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	10.000		Inhalable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	4.000		Respirable aerosol
	NATIONAL	AUSTRALIA	10.000		Inhalable dust containing no asbestos and < 1% crystalline silica
	NATIONAL	AUSTRIA	10.000	20.000	Long term: inhalable fraction; Short term: inhalable fraction, 60 minutes average value
	NATIONAL	AUSTRIA	5.000	10.000	Long term: respirable fraction; Short term: respirable fraction, 60 minutes average value

	NATIONAL	CANADA	10.000				
	NATIONAL	DENMARK	5.000		10.000		Calculated as AI; Long term and Short term: inhalable aerosol
	NATIONAL	DENMARK	2.000		4.000		Calculated as AI; Long term and Short term: respirable aerosol
	NATIONAL	GERMANY	4.000				Inhalable aerosol
	NATIONAL	GERMANY	1.500				Respirable aerosol
	NATIONAL	HUNGARY	6.000				Respirable aerosol
	NATIONAL	IRELAND	10.000				Inhalable fraction
	NATIONAL	IRELAND	4.000				Respirable fraction
	NATIONAL	LATVIA	6.000				
	NATIONAL	NEW ZEALAND	10.000				The value for inhalable dust containing no asbestos and less than 1% free silica
	NATIONAL	POLAND	2.500		16.000		Aluminium trioxide as AI fume; Long term: total dust fume
	NATIONAL	POLAND	1.200				Aluminium trioxide as AI fume; Long term: respirable dust
	NATIONAL	ROMANIA	2.000	0.500	5.000	1.200	Long term and short term: aerosol
	NATIONAL	SINGAPORE	10.000				
	NATIONAL	KOREA, REPUBLIC OF	10.000				
	NATIONAL	SPAIN	10.000				Inhalable aerosol
	NATIONAL	SPAIN	5.000				Respirable aerosol
	NATIONAL	SWEDEN	5.000				Inhalable aerosol
	NATIONAL	SWEDEN	2.000				Respirable aerosol
	NATIONAL	SWITZERLAND	3.000				Respirable aerosol
	NATIONAL	UNITED STATES OF AMERICA	15.000				OSHA; Total dust
	NATIONAL	UNITED STATES OF AMERICA	5.000				OSHA; Inhalable dust
citral	NATIONAL	BELGIUM	32.000	5.000			Long term and short term: inhalable fraction and vapour; Additional indication "D" means that the absorption of the agent through the skin, mucous membranes or eyes is an important part of the total exposure.
	NATIONAL	CANADA		5.000			Ontario; inhalable fraction and vapour
	NATIONAL	POLAND	27.000		54.000		
	NATIONAL	SPAIN		5.000			
	NATIONAL	ITALY	31.000	5.000			
	NATIONAL	IRELAND		5.000			
	NATIONAL	MEXICO		5.000			
	NATIONAL	UNITED STATES OF AMERICA	32.000	5.000			Long term and short term: inhalable fraction and vapour
	ACGIH	NNN		5			(IFV), Skin, DSEN, A4 - Body weight eff, URT irr, eye dam

(R)-p-mentha-1,8-diene	NATIONAL	FINLAND	140.000	25.000	280.000	50.000	
	NATIONAL	GERMANY	28.000	5.000	110.000	20.000	AGS
	NATIONAL	GERMANY	28.000	5.000	112.000	20.000	DFG
	NATIONAL	SWITZERLAND	40.000	7.000	80.000	14.000	
	NATIONAL	NORWAY	140.000	25.000			
	NATIONAL	SLOVENIA	28.000	5.000	112.000	20.000	
	NATIONAL	SPAIN	168.000	30.000			
linalool; 3,7-dimethyl-1,6-octadien-3-ol; dl-linalool	NATIONAL	RUSSIAN FEDERATION			5.000		
2,6-di-tert-butyl-p-cresol	NATIONAL	AUSTRALIA	10.000				
	NATIONAL	AUSTRIA	10.000				
	NATIONAL	BELGIUM	2.000				Inhalable fraction and vapour
	NATIONAL	CANADA	2.000				Ontario; Inhalable fraction and vapour
	NATIONAL	CANADA	10.000				Quebec
	NATIONAL	DENMARK	10.000		20.000		
	NATIONAL	FINLAND	10.000		20.000		
	NATIONAL	FRANCE	10.000				
	NATIONAL	GERMANY	10.000		40.000		ASG; Long term and short term: inhalable aerosol and vapour
	NATIONAL	GERMANY	10.000		40.000		DFG; Long term and short term: inhalable fraction and vapour
	NATIONAL	IRELAND	10.000				
	NATIONAL	NEW ZEALAND	10.000				
	NATIONAL	SINGAPORE	10.000				
	NATIONAL	KOREA, REPUBLIC OF	2.000				
	NATIONAL	SWITZERLAND	10.000				Inhalable aerosol
	NATIONAL	SWITZERLAND			40.000		
	NATIONAL	UNITED STATES OF AMERICA	10.000				NIOSH
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	10.000				
	NATIONAL	ITALY	2.000				
	NATIONAL	ARGENTINA	2.000				Vapour and aerosol
	NATIONAL	BULGARIA	10.000		50.000		
	NATIONAL	CROATIA	10.000				
	NATIONAL	INDONESIA	10.000				
	NATIONAL	ICELAND	10.000				
	NATIONAL	MALAYSIA	10.000				
	NATIONAL	MEXICO	2.000				

NATIONAL	PORTUGAL	2.000	
NATIONAL	SLOVENIA	10.000	40.000
NATIONAL	SPAIN	10.000	
NATIONAL	SOUTH AFRICA	10.000	
ACGIH	NNN	2	(IFV), A4 - URT irr

Predicted No Effect Concentration (PNEC) values

Component	CAS-No.	PNEC Limit	Exposure Route	Exposure Frequency
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	68082-29-1	4.340 µg/l	Freshwater	
		43.400 µg/l	Intermittent releases (freshwater)	
		434.000 ng/L	Marine water	
		3.840 mg/l	Microorganisms in sewage treatments	
		434.020 mg/kg	Freshwater sediments	
		43.400 mg/kg	Marine water sediments	
		86.780 mg/kg	Soil	
Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction	90640-66-7	2.630 µg/l	Freshwater	
		26.300 µg/l	Intermittent releases (freshwater)	
		263.000 ng/L	Marine water	
		7.210 mg/l	Microorganisms in sewage treatments	
		263.010 mg/kg	Freshwater sediments	
		26.301 mg/kg	Marine water sediments	
		58.580 mg/kg	Soil	
Amines, polyethylenepoly-, tetraethylenepentamine fraction	90640-66-7	6.800 µg/l	Freshwater	
		68.000 µg/l	Intermittent releases (freshwater)	
		680.000 ng/L	Marine water	
		4.600 mg/l	Microorganisms in sewage treatments	
		341.000 µg/kg	Freshwater sediments	
		764.000 µg/kg	Marine water sediments	
		274.000 µg/kg	Soil	
titanium dioxide	13463-67-7	0.184 mg/l	Freshwater	
		0.018 mg/l	Marine water	
		1.000 mg/kg	Intermittent releases (freshwater)	
		100.000 mg/kg	Intermittent releases (marine water)	
		100.000 mg/kg	Microorganisms in sewage treatments	
Amines,	90640-67-8	26.800 µg/l	Freshwater	

polyethylenepoly-,
triethylenetetramine
fraction

200.000 µg/l	Intermittent releases (freshwater)
2.680 µg/l	Marine water
20.000 µg/l	Intermittent releases (marine water)
130.000 µg/l	Microorganisms in sewage treatments
8.572 mg/kg	Freshwater sediments
857.200 µg/kg	Marine water sediments
1.250 mg/kg	Soil

Derived No Effect Level (DNEL) values

Component	CAS-No.	Worker Industry	Worker Professional	Consumer	Exposure Route	Exposure Frequency
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	68082-29-1		3.900 mg/m ³	970.000 µg/m ³	Human Inhalation	Long Term, systemic effects
			1.100 mg/kg	560.000 µg/kg	Human Dermal	Long Term, systemic effects
				560.000 µg/kg	Human Oral	Long Term, systemic effects
Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction			3.900 mg/m ³	970.000 µg/m ³	Human Inhalation	Long Term, systemic effects
			1.100 mg/kg	560.000 µg/kg	Human Dermal	Long Term, systemic effects
				560.000 µg/kg	Human Oral	Long Term, systemic effects
Amines, polyethylenepoly-, tetraethylenepentamine fraction	90640-66-7		1.290 mg/m ³	380.000 µg/m ³	Human Inhalation	Long Term, systemic effects
			6940.000 mg/m ³	2071.000 mg/m ³	Human Inhalation	Short Term, systemic effects
			740.000 µg/kg	320.000 µg/kg	Human Dermal	Long Term, systemic effects
				10.000 mg/kg	Human Dermal	Short Term, systemic effects
			0.036 mg/cm ²	0.560 mg/cm ²	Human Dermal	Long Term, local effects
				1.290 mg/cm ²	Human Dermal	Short Term, systemic effects
				530.000 µg/kg	Human Oral	Long Term, systemic effects
	26.000 mg/kg	Human Oral	Short Term, systemic effects			
titanium dioxide	13463-67-7		10.000 mg/m ³		Human Inhalation	Long Term, local effects
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8		540.000 µg/m ³	96.000 µg/m ³	Human Inhalation	Long Term, systemic effects

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Nitrile rubber .

Respiratory protection:

N.A.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Liquid

Color: Yellow

Odour: Like: Amines

Odour threshold: N.A.

pH: Not Relevant

Kinematic viscosity: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: > 90 °C (194 °F)

Flash point: Not Applicable

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 1.62 g/cm³

Solubility in water: Miscible

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Flammability: N.A.

Volatile Organic compounds - VOCs = 0.94 % ; 15.27 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

Miscibility: N.A.

Conductivity: N.A.

Evaporation rate: N.A.

Viscosity: 14,000.00 cPo

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicological Information of the Preparation**

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified
	Based on available data, the classification criteria are not met
c) serious eye damage/irritation	The product is classified: Eye Dam. 1(H318)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1A(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	a) acute toxicity	LD50 Oral Rat > 2000.00000 mg/kg	
		LD50 Skin Rat > 2000.00000 mg/kg 24h	
	c) serious eye damage/irritation	Eye Irritant Yes 1h	
	d) respiratory or skin sensitisation	Eye Corrosive Rabbit Positive Skin Sensitization Positive	Mouse
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 1000.00000 mg/kg	
Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction	a) acute toxicity	LD50 Oral Rat > 2000.00000 mg/kg	
		LD50 Skin Rat > 2000.00000 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Negative	
	c) serious eye damage/irritation	Eye Corrosive Positive	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 1000.00000 mg/kg	
Alcohols, C12-15, branched and linear, ethoxylated	a) acute toxicity	LD50 Oral > 300.00 mg/kg	

Amines, polyethylenepoly-, tetraethylenepentamine fraction	a) acute toxicity	LD50 Oral Rat = 1861.90000 mg/kg	
		LD50 Skin Rabbit = 1465.40000 mg/kg 24h	
	b) skin corrosion/irritation	Skin Corrosive Rabbit Positive	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Positive	
	f) carcinogenicity	Genotoxicity Negative	Mouse intraperitoneal route
	g) reproductive toxicity	Reproductive Toxicity Oral Rat Negative	
Quartz	a) acute toxicity	LD50 Oral > 2000.00000 mg/kg	
titanium dioxide	a) acute toxicity	LD50 Oral Rat > 5000.00 mg/kg	
		LC50 Inhalation > 6.82 mg/l	
	d) respiratory or skin sensitisation	Skin Sensitization Negative	
	i) STOT-repeated exposure	No Observed Adverse Effect Level 1000.00	
Amines, polyethylenepoly-, triethylenetetramine fraction	a) acute toxicity	LD50 Oral Rat = 1716.20000 mg/kg	
		LD50 Skin Rabbit = 1465.40000 mg/kg 24h	
	b) skin corrosion/irritation	Skin Corrosive Rabbit Positive	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Guineapig Positive	
	f) carcinogenicity	Genotoxicity Negative	Mouse intraperitoneal route
		Carcinogenicity Skin = 50.00000 mg/kg	Mouse NOAEL

11.2 Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Harmful to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	CAS: 68082-29-1 - EINECS: 500-191-5	a) Aquatic acute toxicity : LC50 Fish = 10.00 mg/L 96h a) Aquatic acute toxicity : EC100 Daphnia = 10.00 mg/L 24h a) Aquatic acute toxicity : EC50 Algae = 4.34 mL/L 72h
Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-	EINECS: 701-046-0	a) Aquatic acute toxicity : LC50 Fish Zebrafish = 7.07000 mg/L 96h OECD 203

tetraethylenepentamine fraction

		a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 5.18000 mg/L 48h OECD 202
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 2.63000 mg/L 72h OECD 201
		a) Aquatic acute toxicity : EC50 Sludge Activated sludge = 721.00000 mg/L 3h OECD 209
		c) Bacteria toxicity : NOEC 1.41000 mg/L
Alcohols, C12-15, branched and linear, ethoxylated	CAS: 106232-83-1	a) Aquatic acute toxicity : LC50 Fish Carassius Auratus < 10.00 mg/L 96h CESIO
Amines, polyethylenepoly-, tetraethylenepentamine fraction	CAS: 90640-66-7 - EINECS: 292-587-7	a) Aquatic acute toxicity : EC50 Honeybees Daphnie < 10.00 mg/L 48h CESIO a) Aquatic acute toxicity : LC50 Fish freshwater fish = 420.00000 mg/L
titanium dioxide	CAS: 13463-67-7 - EINECS: 236-675-5 - INDEX: 022-006-00-2	a) Aquatic acute toxicity : LC50 freshwater invertebrates = 24.10000 mg/L a) Aquatic acute toxicity : EC50 Algae freshwater algae = 6.80000 mg/L a) Aquatic acute toxicity : EC50 microorganisms = 97.30000 mg/L a) Aquatic acute toxicity : NOEC Algae = 0.50000 mg/L a) Aquatic acute toxicity : LC50 Fish Pimephales promelas (Cavedano americano) > 1000.00 mg/L 96h a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata (alghe cloroficee) > 100.00 mg/L 72h a) Aquatic acute toxicity : NOEC Algae = 5600.00 mg/L a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna (Pulce d'acqua grande) > 100.00 mg/L 48h
Amines, polyethylenepoly-, triethylenetetramine fraction	CAS: 90640-67-8 - EINECS: 292-588-2 - INDEX: 612-059-00-5	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 330.00000 mg/L 96h „U.S EPA- TSCA, 40 CFR Part 797 1400 a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 31.10000 mg/L 48h EU Method C.2 (Acute Toxicity for Daphnia) a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 20.00000 mg/L 72h OECD 201 d) Terrestrial toxicity : NOEC Worm Eisenia fetida = 62.50000 mg/kg OECD Guideline 222 (Earthworm Reproduction Test (Eisenia fetida/Eisenia andrei)) - 56days a) Aquatic acute toxicity : NOEC Algae soil microorganisms = 72.00000 mg/L

12.2. Persistence and degradability

Component	Persistence/Degradability:	Duration	Notes
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Non-readily biodegradable		OECD 301 D
Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction	Non-readily biodegradable		
Alcohols, C12-15, branched and linear, ethoxylated	Readily biodegradable	28d	>70% (OECD tg 301 B)
Amines, polyethylenepoly-, tetraethylenepentamine fraction	Non-readily biodegradable		
Amines, polyethylenepoly-, triethylenetetramine fraction	Non-readily biodegradable		OECD 301D

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Value	Notes
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Bioaccumulative	BCF - Bioconcentration factor	77.400	L/kg ww; QSAR
Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction	Bioaccumulative	BCF - Bioconcentration factor	138.000	L/kg ww

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7 Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

A waste code according to European waste catalogue (EWC) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

HP 13: Sensitising; HP 14: Ecotoxic; HP 4: Irritant — skin irritation and eye damage

SECTION 14: Transport information

14.1. UN number or ID number

N/A

14.2. UN proper shipping name

ADR-Shipping Name: N/A

IATA-Technical name: N/A

IMDG-Technical name: N/A

14.3. Transport hazard class(es)

ADR-Class: N/A

IATA-Class: N/A

IMDG-Class: N/A

14.4. Packing group

ADR-Packing Group: N/A

IATA-Packing group: N/A

IMDG-Packing group: N/A

14.5. Environmental hazards

Marine pollutant: No

Environmental Pollutant: No

IMDG-EMS: N/A

14.6. Special precautions for user

Road and Rail (ADR-RID) :

ADR-Label: N/A

ADR - Hazard identification number: N/A

ADR-Special Provisions: N/A

ADR-Transport category (Tunnel restriction code): N/A

ADR Limited Quantities: N/A

ADR Excepted Quantities: N/A

Air (IATA) :

IATA-Passenger Aircraft: N/A

IATA-Cargo Aircraft: N/A

IATA-Label: N/A

IATA-Subsidiary hazards: N/A
IATA-Erg: N/A
IATA-Special Provisioning: N/A

Sea (IMDG) :

IMDG-Stowage Code: N/A
IMDG-Stowage Note: N/A
IMDG-Subsidiary hazards: N/A
IMDG-Special Provisioning: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 28, 40, 75

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

Regulation (EU) 649/2012 (PIC regulation):

No Substance Listed

German Water Hazard Class.

Class 1: slightly hazardous for water.

SVHC Substances:

No data available

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
EUH071	Corrosive to the respiratory tract.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

H318	Causes serious eye damage.
EUH212	Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1-1A-1B	Skin Sens. 1,1A,1B	Skin Sensitisation, Category 1,1A,1B
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category 1
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
3.3/1	Calculation method
3.4.2/1A	Calculation method
4.1/C3	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive
DSD: Dangerous Substances Directive
EC50: Half Maximal Effective Concentration
ECHA: European Chemicals Agency
EINECS: European Inventory of Existing Commercial Chemical Substances.
ES: Exposure Scenario
GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
IRCCS: Scientific Institute for Research, Hospitalization and Health Care
KAFH: Keep Away From Heat
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LDLo: Leathal Dose Low
N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration.
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.